

92 Thomas Johnson Drive, Suite 230, Frederick, MD 21702

Phone: 301-695-2803 Ext. 3 Fax: 301-694-0270

Email: soil.conservation@comcast.net

POND CODE 378 CHECKLIST FOR SMALL POND APPROVAL

SCD Project Number	Date
Applicant	
Project Name	
Design Firm	

PLEASE NOTE THAT PLANS SUBMITTED WITHOUT A COMPLETED CHECKLIST MAY BE RETURNED WITHOUT REVIEW

	esigne neck of		Technical Reviewer		Carlandaria IA				
YES	NO	N/A	received (yes/no)	correct (yes/no)	Submission Item				
					SUBMISSION DOCUMENTS				
					Point by point responses to comment letter (if applicable)				
					Pond 378 construction plan set with Professional Engineer's certification, seal, signature, and date Stormwater management design report with Professional Engineer's certification, seal, signature, and date				
					Geotechnical report for stormwater management pond with Professional Engineer's certification, seal, signature, and date				
					Dam breach analysis for small ponds with Professional Engineer's certification, seal, signature, and date				
					Pond Summary Sheet (MD-ENG-14)				
				Approved erosion and sediment control plans from local soil conservation district					
					Stormwater Management (SWM) approval from the local approval authority as required.				

1800 Washington Boulevard | Baltimore, MD 21230 | 1-800-633-6101 | 410-537-3000 | TTY Users 1-800-735-2258 www.mde.maryland.gov

	esigne heck of			nical ewer	Submission Itom			
YES	NO	N/A	received (ves/no)	correct (yes/no)	Submission Item			
			() <i>(20)</i>	(j es. 220)	CONSTRUCTION PLANS			
					TITLE SHEET(S)			
					Project name, street address, zoning, tax map, election district, parcel no., latitude, longitude			
					Owner/Developer name, address and phone number			
					Design Professional name, address and phone number			
					MDE Permit No.			
				MDE Tracking No.				
					MDE Agency Interest No.			
					Vicinity map to scale (1"=2000') with major roads identified an site delineated			
					Legend			
					Sheet index			
					Professional Engineer's certification, seal, signature, and date			
					OTHER			
					Construction specifications per MD Code 378 (Site Prep, Earth Fill, Structural Backfill, Pipe Conduits, Concrete, Stabilization)			
					As-built tables			
					As-built certification block			
					Construction inspection schedule			
					Maintenance schedule			
					GENERAL INFORMATION (ALL SHEETS)			
					Plan scale range: 1 " = 10 ' to 1 " = 50 '			
					Profile scale: 1" - 5' vertical, to 1" = 50' horizontal			
					Maximum Drawing Size: 24" x 36"			
					Minimum 3 grid ticks with lat/long on plan sheets			
					North arrow			
					Match lines labeled and referenced			
					Profiles, details, and cross-sections drawn to scale			
					Sheets numbered, consecutively; revisions noted with date			

Designer (check off)			Technical Reviewer				
YES	NO	N/A	received	correct	Submission Item		
			(yes/no)	(yes/no)	MDE Permit No.		
					Professional Engineer's certification, seal, signature, and date		
					PLAN VIEW OF POND AT SCALE OF 1" = 50' OR LESS show and label the following:		
					Existing and final contours (2' interval maximum) with index contours clearly labeled		
					Locations of test borings and bench mark (1 in dam centerline (min); 1 in emergency spillway(min))		
					Inflow channel or pipe; erosion protection		
					Outflow pipe, outlet protection, outfall channel		
					Property lines and easements with owners information		
					Low flow channel (if applicable)		
					Emergency spillway and outlet channel		
					Stationing of embankment centerline; location of other section details		
					Site features and existing/proposed grading to 200 ft beyond pond limits		
					"No woody vegetation" zone delineated		
					Storm drainage system, size, material (existing and proposed) with easements clearly identified		
					Downstream conveyance system (existing and proposed) with easements clearly identified		
					Utilities (existing and proposed) with easements clearly identified		
					Floodplain limits with sections and water surface elevations		
					Wetland boundary and wetland buffer labeled		
					CBCA Boundary labeled		
				Waters of the U.S. labeled			
				Forest conservation easements labeled			
					Sinkholes and rock outcrops labeled		
					Forebays and internal berms (reference berm detail)		
					Control structure (reference detail)		

	esigne neck of		Technical Reviewer				
YES	NO	N/A	received (yes/no)	correct (yes/no)	Submission Item Principal spillway		
			Q 22, 22 2)	() 02.220)	Principal spillway		
					Seepage control (reference detail)		
					Limits of clay core trench		
					Pond maintenance access		
					Fencing (if applicable)		
					Trash rack/low flow trash rack (reference detail)		
					Limits of pond liner (if applicable)		
					Benching for ponds deeper than 4 feet		
				CROSS-SECTION OF DAM ALONG PRINCIPAL SPILLWAY (i.e. profile of principal spillway) – show and label the following:			
					Existing and proposed ground surface		
					Slope of embankment sides $(2:1 \text{ max})/(5:1 \text{ max combined for top width} \le 26 \text{ ft})$		
					Embankment top width (6' minimum; 10-26' for road); top elevation		
					Cutoff trench (dimensioned); bottom width 4' minimum; side slopes 1:1 maximum; depth 4' minimum below concrete cradle		
					Impervious Core (up to 10 year WSEL); side slopes; top width; top elevation		
					Control structure (and reference detail location)		
					Trash rack (all openings in control structure; reference detail)		
					SWM Design WSEL (Design High Water (DHW))		
					Permanent pool WSEL		
					100-yr WSEL		
					Control structure openings: diameter or dimensions		
					Principal spillway pipe (barrel): inside diameter or dimensions; length; slope; invert in and out		
					Material: for concrete pipe, ASTM C-361; for PVC pipe, ASTM D-1785 or D-2241; for HDPE, AASHTO M294 Type S; for HDPE ≤ 10", AASHTO M252 Type S		
					Specify water tight joints		

	esigne neck of		Tech Revi	nical ewer	Cubusiasion Idona
YES	NO	N/A	received correct (yes/no) (yes/no) Submission Item		Submission Item
			(Jesi III)	(j esi iio)	CROSS-SECTION OF DAM ALONG PRINCIPAL SPILLWAY (i.e. profile of principal spillway) – show and label the following:
					Existing and proposed ground surface
					Slope of embankment sides $(2:1 \text{ max})/(5:1 \text{ max combined for top width} \le 26 \text{ ft})$
					Embankment top width (6' minimum; 10-26' for road); top elevation
					Cutoff trench (dimensioned); bottom width 4' minimum; side slopes 1:1 maximum; depth 4' minimum below concrete cradle
					Impervious Core (up to 10 year WSEL); side slopes; top width; top elevation
					Control structure (and reference detail location)
					Trash rack (all openings in control structure; reference detail)
					SWM Design WSEL (Design High Water (DHW))
					Permanent pool WSEL
					100-yr WSEL
					Control structure openings: diameter or dimensions
					Principal spillway pipe (barrel): inside diameter or dimensions; length; slope; invert in and out
					Material: for concrete pipe, ASTM C-361; for PVC pipe, ASTM D-1785 or D-2241; for HDPE, AASHTO M294 Type S; for HDPE ≤ 10", AASHTO M252 Type S
					Specify water tight joints
					Phreatic line (4:1 slope from 10 year WSEL); saturated length
					Filter diaphragm (reference detail location);
					Bedding (if pipe is concrete) (detail required)
					Outlet protection: median riprap size (d ₅₀); thickness; length, width; cross-section detail (reference location); filter cloth
					Design Qs and velocities
					Specification of construction height and <u>settled</u> height for dam construction elevations
					Freeboard (min 1ft above DHW, or min 2 ft without emergency spillway)

	Designer (check off)		Technical Reviewer		Submission Item			
YES	NO	N/A	received (yes/no)	correct (yes/no)	Submission item			
			(yes/no)	(yes/110)	PROFILE OF EMERGENCY SPILLWAY detail drawn to scale to show and label the following:			
					Existing and proposed ground surface. Locate on natural ground or in cut. Otherwise, use weir or pass through principal spillway.			
					Invert elevations - inlet, control and outlet sections			
					Length of inlet, control, and outlet sections			
					Slopes of inlet, control and outlet sections			
					Design Q and velocity			
					Cross-section detail of emergency spillway with invert (crest) elevation, 100 year WSEL, bottom width, existing and proposed ground surface, side slopes labeled.			
					Proper protection of spillway			
					Protection of channel including material type and size			
					CROSS-SECTION OF DAM ALONG CENTERLINE drawn to scale and stationed to show the following:			
					Top of dam and elevation			
					Location of principal spillway with concrete cradle			
					Existing ground			
					Proposed ground			
					Top of core and elevations; limits shaded			
					Bottom of cutoff trench and elevation; limits shaded			
					Location and crest elevation of emergency spillway (shown in cut)			
					100 year and 10 year WSELs denoted			
					CONTROL STRUCTURE DETAIL			
					Material specified (same as principal spillway pipe); thickness or gage (if metal)			
				Riser crest elevation and invert elevations of all openings				
					All openings dimensioned			
					Inside dimensions (diameter or width, length, height)			
					Concrete collar shown and labeled			
					Key joint detail			

	Designer (check off)		Technical Reviewer					
YES	NO	N/A	received (yes/no)	correct (yes/no)	Submission Item			
			() <i>(5,110)</i>	(j es/110)	Riser base: length, width, thickness or gage (if metal)			
					Key joint detail			
					Depth of embedding			
					Low flow orifice anchor and support labeled			
					Dewatering device shown and labeled (reference detail)			
					Show and label trash rack – all openings. (reference detail)			
					TRASH RACK DETAIL(S)			
					Material specified; galvanized and removable			
					Opening sizes dimensioned			
					Extension required on top flow inlet structures (no flat trash racks)			
					Anti-vortex device (for cylindrical trash racks)			
					FILTER DIAPHRAGM DETAIL			
					Drain material noted; ASTM C-33 sand			
					Extend to normal pool WSEL			
					Dimensions – width (minimum 3D from outer principal spillway pipe); height (minimum 3D above outer diameter of pipe and 18 inches below outer diameter of pipe); thickness (2 feet min.)			
					Minimum 2 ft. cover			
					Pressure relief drain pipe diameter, material, perforations			
					GATE VALVE DETAIL			
					Valve stem to top of structure and accessible			
					Valve stem anchored			
					Specify material			
					STORM DRAINAGE PROFILES (inflow systems, systems through pond, systems adjacent to pond)			
					Structures numbered and stationed			
					Size and inverts of all pipes at the structure			
					Structure inverts labeled upstream and downstream at each structure			
					10 year hydraulic grading shown and labeled			

	Designer (check off)		Technical Reviewer		Submission Item
YES	NO	N/A	received (yes/no)	correct (yes/no)	Submission item
			(Jes/110)	(Jesi III)	Label limits of road, pavement, right-of-way above profile
					Existing and finished ground line at centerline of storm drain shown
					Structure and pipe schedules
					LANDSCAPING PLAN
					Include plant material, number, spacing, location, and size.
					"No woody vegetation" zone delineated
					REPORTS AND CALCULATIONS
					SOILS INVESTIGATION REPORT
					Borings along centerline of dam and in the borrow area
					Use of Unified Soil Classification System
					Determination of seepage potential
					Determination of bearing strength, if soil is an unstable clay
					Log on dam profile and plan view
					Blow counts, elevations, and location of ground water
					HYDROLOGY
					Existing and ultimate conditions drainage area map (1" = 200' scale or less):
					Existing and ultimate drainage area (DA) limits delineated
					Existing and ultimate land uses delineated
					Existing and ultimate time of concentration paths shown
					USDA Soils map (site and DA delineated)
					Runoff computations
					Hydrologic Soil Groups
					Existing RCN and ultimate RCN
				Time of concentration (existing and ultimate)	
					Existing and ultimate development hydrographs for 10 and 100 year storms
					POND HYDRAULICS/ROUTINGS
					Basin routing using short cut method or storage indication

	esigne neck of		Technical Reviewer		Carlandarian Idam			
YES	NO	N/A	received (yes/no)	correct (yes/no)	Submission Item			
			7	<u> </u>	Stage - storage table and curve for pond to top of embankment			
					HY8 or culvert capacity analysis			
					Stage (elevation) - discharge table for pond			
					Inflow hydrograph NOAA Atlas 14			
					Routed discharges for 10-yr and 100-yr storms			
					Discharge velocities and outfall channel protection sizing (10-yr storm)			
					Anti-flotation computations for riser, FOS ≥ 1.2			
					EMERGENCY SPILLWAY			
					Capacity of principal spillway and emergency spillway sized by Code 378			
					Reference ESC handbook Design by Engineering Field Manual, pps 11-34.1 through 11-54.11			
					OUTFALL STUDY			
					Existing vegetation and condition			
					Flow rates and velocities, after development, for 10-yr and 100-yr storms			
					Elevation at end of outlet protection			
					Property lines, easements, utility crossings, floodplain limits, waters of US, wetlands and wetland buffers, location and first floor elevation of critical structures.			
					DAM BREACH ANALYSIS			
					Danger reach study per the following guidance: https://mde.maryland.gov/programs/water/DamSafety/Documents /Dam-Breach-Analysis/2018-05-15-Breach-Analysis- Guidance.pdf			
					Cross sections at critical points (in improved and existing channel)			
					Check mapping for additional ponds or embankments in flow path and hazard creep			
					d≤ 1.5 feet, Class "a" structure			

ADDITIONAL NOTES:				